# **HyFlex® 11-800**

## TECHNICAL DATASHEET

Multi-purpose Print date 04-02-2014

#### **Glove material**

- Foam nitrile (Coating material)
- Nylon (Liner material)

## **Possible Harmful ingredients**

Sensitizers

No sensitizers

## Reach Regulation 1907/2006

For more information, please consult the REACH statement on the Ansell website

#### **Properties**

- Good oil grip
- Superior comfort due to the absence of seams in the knitted liner
- Superior flexibility and dexterity due to the thin membrane
- Superior abrasion resistance

#### **EN Test Data**

#### Abrasion resistance:

Performance level 3

## Blade cut resistance:

Performance level 1

## Tear resistance:

Performance level 3

## Puncture resistance:

Performance level 1

## **European conformity**

Gloves conform to the requirements of the European Directive 89/686/EEC and to the European standards EN 420:2003 + A1:2009 and EN 388:2003

They are categorised in "Intermediate Design" (= Protection against intermediate risks).

EC-Type Examination Certificate for the final product by Centexbel

Technologiepark 7 B-9052 Zwijnaarde

## **Application - Limitations of use**

Hand protection – light to medium duty applications

Do not use against flames or temperatures < - 25°C or > 100°C

Do not use for heavy duty mechanical applications

Do not use against chemicals; the glove is not liquid

#### **Storage**

Keep away from sources of ozone or ignition. Keep out of direct sunlight; store in a cool and dry place.

Constructio n	Gauge	Liner material	Coating material	Finishing	Cuff style	Colour	EN Size	Length mm	Packaging
Knitted	15	Nylon	Foam nitrile	Palm coated	Knitwrist	Grey and white	6, 7, 8, 9, 10, 11	200 - 265	12 pairs in a bag; 12 bags in a carton

The length of the gloves is below the EN requirements for total minimum glove length. Hence, the glove is called 'Fit for special purpose'

